

ENBO RNP-B - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	LISSU	-	-	-6.0	-	-	-	A5700+	-	-	-	1.0
20	TF	OMAKI	-	-	-6.0	5.0	-	-	A4600+	-	-	-	1.0
10	IF	VITRE	-	-	-6.0	-	-	-	A5400+	-	-	-	1.0
20	TF	OMAKI	-	-	-6.0	5.0	-	-	A4600+	-	-	-	1.0
10	IF	OMAKI	-	-	-6.0	-	-	-	A4600+	-	-	-	1.0
20	TF	BO811	-	-	-6.0	4.4	-	-	A4000+	-	-	-	1.0
30	TF	BO812	Y	-	-6.0	5.6	-	-	-	-	-3.9	-	0.3
40	TF	BDO	Y	-	-6.0	2.0	-	-	-	-	-	-	1.0
50	FA	BDO	-	239 (245.0)	-6.0	-	BOO	-	A4000	-	-	-	1.0
60	DF	BDO	-	-	-6.0	-	-	R	-	-	-	-	1.0
70	HM	BDO	-	252 (258.0)	-6.0	1 MIN	-	R	A4400	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.